

ISOVP/ISOVP-L/GEVP ACCESSORIES

SMB-PC

SMB PIGTAIL CABLE



GEVP

ISOVP

ISOVP-L

- SMB to coaxial cable for user made connections
- 15/30 cm lengths, others on request
- Meets IEC 61010-31
- Adds 1pF/cm capacitance

Item	Length
SMB-PC15	15cm
SMB-PC30	30cm



SMB-GRB

SMB TO GRABBERS



GEVP

ISOVP

ISOVP-L



- Grabbers to SMB connector cable
- Touch protected cable
- Meets IEC 61010-31
- Useful for generic fast connections to board

SMB-EXT

SMB EXTENDER



GEVP

ISOVP

ISOVP-L

- SMB male to SMB female extender coaxial cable with touch protected connectors
- 15/30 cm lengths, others on request
- Meets IEC 61010-31
- Adds 1pF/cm capacitance

Item	Length
SMB-EXT15	15cm
SMB-EXT30	30cm



ISOVP50**X50 ATTENUATOR****ISOVP****ISOVP-L**

- SMB input, SMB output
- x50 attenuation.
- 1MΩ || 5pF, ±125V, MAX DC + pk AC 250V
- Not to be used for handheld measurements >60VDC

ISOVP10**X10 ATTENUATOR****ISOVP****ISOVP-L**

- SMB input, SMB output
- x10 attenuation.
- 1MΩ || 5pF, ±25V, MAX DC + pk AC 150V
- Not to be used for handheld measurements >60VDC

ATTx100**X100 ATTENUATOR**

- 10M0hm input
- 1500V max input, x100 attenuation.
- HRG58-20 input coaxial cable
- SMB output

GEVP**ISOVP****ISOVP-L**

GEVP-OSC**SQUARE WAVE OSCILLATOR**

GEVP

ISOVP-L



- Square wave oscillator with precise zero and 2.5V levels to calibrate the GEVP/ISOVP-L probes
- Auto power-off
- SMB output
- Runs on a CR1225 battery

TERM50**50 OHM TERMINATION**

GEVP

ISOVP

ISOVP-L



- 50 Ohm BNC termination for scopes

EXTBATT**EXTERNAL BATTERY PACK**

ISOVP

ISOVP-L



- External rechargeable battery pack for ISOVP probes
- 2 internal 18650 batteries, >6000mAh total
- Input/output fuse protected
- Includes camera thread mount
- Includes external universal AC/DC adapter.



ISOVP

ISOVP-L

- Hard transport case for the ISOVP probe